

This safety data sheet was created pursuant to the requirements of:
UK REACH Regulations (SI 2019/758 as amended)

Revision date 04/06/2024

Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code(s) BES1A
Product Name Bradex Easy Start
Pure substance/mixture Mixture

Contains Ethyl ether, Naphtha (petroleum),hydrotreated light, DI-ISOPROPYL ETHER, Acetone, DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U, Propane, Isobutane

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Car Maintenance Product
Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Supplier
Holts Auto
Unit 100 Barton Dock Road
Manchester
United Kingdom
M32 0YQ

For further information, please contact

Contact Point www.holtsauto.com
E-mail address www.holtsauto.com

1.4. Emergency telephone number

Emergency Telephone No information available

United Kingdom	Holt Lloyd International: UK - 00 44 (0) 161 866 4800 Office Hours - Mon - Thurs: 8am - 5pm. Fri - 8am - 1pm. 00 44 (0) 161 886 4806 (24 Hour Voicemail).
-----------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosols	Category 1 - (H222, H229)
-----------------	---------------------------

Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains Ethyl ether, Naphtha (petroleum),hydrotreated light, DI-ISOPROPYL ETHER, Acetone, DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U, Propane, Isobutane



Signal word

Danger

Hazard statements

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects
EUH019 - May form explosive peroxides
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing spray
P271 - Use only outdoors or in a well-ventilated area
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

Unknown aquatic toxicity

Contains 0 % of components with unknown hazards to the aquatic environment.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	EC No (EU Index No)	UK REACH registration number	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)
Ethyl ether 60-29-7	25 - <50%	200-467-2 (603-022-00-4)	-	(EUH019) (EUH066) Flam. Liq. 1 (H224) Acute Tox. 4 (H302) STOT SE 3 (H336)	-	-	-
Naphtha (petroleum),hydrotreated light 64742-49-0	10 - <25%	265-151-9 (649-328-00-1)	-	Flam. Liq. 2 (H225) Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)	-	-	-
DI-ISOPROPYL ETHER 108-20-3	10 - <25%	203-560-6 (603-045-00-X)	-	(EUH019) (EUH066) Flam. Liq. 2 (H225) STOT SE 3 (H336)	-	-	-
Acetone 67-64-1	5 - <10%	200-662-2 (606-001-00-8)	-	(EUH066) Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	-	-	-
n-Butane 106-97-8	5 - <10%	203-448-7 (601-004-00-0)	-	Flam. Gas 1 (H220) Press. Gas ()	-	-	-
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U 64742-52-5	5 - <10%	265-155-0 (649-465-00-7)	-	-	-	-	-
Propane 74-98-6	5 - <10%	200-827-9 (601-003-00-5)	-	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-
Isobutane 75-28-5	2.5 - <5%	200-857-2 (601-004-00-0)	-	Flam. Gas 1 (H220) Press. Gas	-	-	-
PYRIDINE 110-86-1	0.025 - <0.25%	203-809-9 (613-002-00-7)	-	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam. Liq. 2 (H225)	-	-	-

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (UK REACH Article 59)

SECTION 4: First aid measures**4.1. Description of first aid measures****General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.

Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a doctor.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Treat symptomatically.
------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.
---	--

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.
-----------------------------	--

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up.

7.3. Specific end use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	United Kingdom
Ethyl ether 60-29-7	TWA: 100 ppm TWA: 310 mg/m ³ STEL: 200 ppm STEL: 620 mg/m ³
DI-ISOPROPYL ETHER 108-20-3	TWA: 250 ppm TWA: 1060 mg/m ³ STEL: 310 ppm STEL: 1310 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
n-Butane 106-97-8	TWA: 600 ppm TWA: 1450 mg/m ³ STEL: 750 ppm STEL: 1810 mg/m ³
PYRIDINE 110-86-1	TWA: 5 ppm TWA: 16 mg/m ³ STEL: 10 ppm STEL: 33 mg/m ³

Biological occupational exposure limits This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies.

Derived No Effect Level (DNEL) - Workers

Chemical name	Oral	Dermal	Inhalation
Ethyl ether 60-29-7		44 mg/kg bw/day [4] [6]	308 mg/m ³ [4] [6] 616 mg/m ³ [4] [7]
Naphtha (petroleum),hydrotreated light 64742-49-0			1286.4 mg/m ³ [4] [7] 837.5 mg/m ³ [5] [6] 1066.67 mg/m ³ [5] [7]
DI-ISOPROPYL ETHER 108-20-3		121.4 mg/kg bw/day [4] [6]	850 mg/m ³ [4] [6] 1700 mg/m ³ [4] [7]
Acetone 67-64-1		186 mg/kg bw/day [4] [6]	1210 mg/m ³ [4] [6] 2420 mg/m ³ [5] [7]
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U 64742-52-5		0.97 mg/kg bw/day [4] [6]	2.73 mg/m ³ [4] [6] 5.58 mg/m ³ [5] [6]
PYRIDINE 110-86-1		0.14 mg/kg bw/day [4] [6] 0.42 mg/kg bw/day [4] [7]	2.5 mg/m ³ [4] [6] 7.5 mg/m ³ [4] [7]

Notes

[4] Systemic health effects.
[5] Local health effects.
[6] Long term.

[7] Short term.

Derived No Effect Level (DNEL) - General Public

Chemical name	Oral	Dermal	Inhalation
Ethyl ether 60-29-7	15.6 mg/kg bw/day [4] [6]		54.5 mg/m ³ [4] [6]
Naphtha (petroleum),hydrotreated light 64742-49-0			1152 mg/m ³ [4] [7] 178.57 mg/m ³ [5] [6] 640 mg/m ³ [5] [7]
DI-ISOPROPYL ETHER 108-20-3	43.1 mg/kg bw/day [4] [6]		151 mg/m ³ [4] [6] 302 mg/m ³ [4] [7]
Acetone 67-64-1	62 mg/kg bw/day [4] [6]		200 mg/m ³ [4] [6]
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U 64742-52-5	0.74 mg/kg bw/day [4] [6]		1.19 mg/m ³ [5] [6]
PYRIDINE 110-86-1	0.07 mg/kg bw/day [4] [6]		0.6 mg/m ³ [4] [6]

Notes

[4] Systemic health effects.
 [5] Local health effects.
 [6] Long term.
 [7] Short term.

Predicted No Effect Concentration (PNEC)

Chemical name	Freshwater	Freshwater (intermittent release)	Marine water	Marine water (intermittent release)	Air
Ethyl ether 60-29-7	2 mg/L	1.65 mg/L	0.2 mg/L		
DI-ISOPROPYL ETHER 108-20-3	0.19 mg/L	1.9 mg/L	0.019 mg/L		
Acetone 67-64-1	10.6 mg/L	21 mg/L	1.06 mg/L		
PYRIDINE 110-86-1	0.3 mg/L	3 mg/L	0.03 mg/L		

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
Ethyl ether 60-29-7	9.14 mg/kg sediment dw	0.914 mg/kg sediment dw	4.2 mg/L	0.66 mg/kg soil dw	
DI-ISOPROPYL ETHER 108-20-3	2.79 mg/kg sediment dw	0.28 mg/kg sediment dw	37 mg/L	0.47 mg/kg soil dw	
Acetone 67-64-1	30.4 mg/kg sediment dw	3.04 mg/kg sediment dw	100 mg/L	29.5 mg/kg soil dw	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U 64742-52-5					9.33 mg/kg food

Chemical name	Freshwater sediment	Marine sediment	Sewage treatment	Soil	Food chain
PYRIDINE 110-86-1	3.2 mg/kg sediment dw	0.32 mg/kg sediment dw	2 mg/L	0.46 mg/kg soil dw	

8.2. Exposure controls

Engineering controls No information available.

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Safety glasses with side shields are recommended for medical or industrial exposures.

Hand protection Impervious gloves. Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state Aerosol
Appearance Aerosol
Colour Colourless
Odour Ether.
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	-38 °C	None known
Autoignition temperature	170 °C	180°C
Decomposition temperature		None known
pH	No data available	None known
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Water solubility	Immiscible in water	None known
Solubility(ies)	No data available	None known

Partition coefficient	No data available	None known
Vapour pressure	3500 hPa @ 20°C	None known
Relative density	0.7 g/cm ³ @20°C	None known
Bulk density	No data available	
Liquid Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
Explosive properties	No information available	
Oxidising properties	No information available	

9.2. Other information**SECTION 10: Stability and reactivity****10.1. Reactivity**

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Information on likely routes of exposure****Product Information**

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based

on components).

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	3,617.10 mg/kg
ATEmix (dermal)	7,000.00 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapour)	99,999.00 mg/l
ATEmix (inhalation-dust/mist)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl ether	= 1215 mg/kg (Rat)	> 20000 mg/kg (Rabbit)	= 32000 ppm (Rat) 4 h
Naphtha (petroleum),hydrotreated light	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat) 4 h
DI-ISOPROPYL ETHER	= 4700 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
n-Butane	-	-	= 658 g/m ³ (Rat) 4 h
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Propane	-	-	> 800000 ppm (Rat) 15 min
Isobutane	-	-	> 800000 ppm (Rat) 15 min
PYRIDINE	= 866 mg/kg (Rat)	1000 - 2000 mg/kg (Rabbit)	= 12.898 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation

No information available.

Respiratory or skin sensitisation

No information available.

Germ cell mutagenicity

Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as mutagenic.

Chemical name	United Kingdom
Naphtha (petroleum),hydrotreated light	Muta. 1B
n-Butane	Muta. 1B
Propane	Muta. 1B
Isobutane	Muta. 1B

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	United Kingdom
Naphtha (petroleum),hydrotreated light	Carc. 1B
n-Butane	Carc. 1A
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U	Carc. 1B
Propane	Carc. 1A
Isobutane	Carc. 1A

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Unknown aquatic toxicity Contains 0 % of components with unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl ether	-	LC50: =2560mg/L (96h, Pimephales promelas) LC50: >10000mg/L (96h, Lepomis macrochirus)	-	-
Naphtha (petroleum),hydrotreated light	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	EC50: <0.26mg/L (48h, Daphnia magna)
DI-ISOPROPYL ETHER	-	LC50: =91.7mg/L (96h, Pimephales promelas) LC50: =7000mg/L (96h, Lepomis macrochirus)	-	EC50: =190mg/L (48h, Daphnia magna)
Acetone	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h,	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U	-	Lepomis macrochirus) LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
PYRIDINE	-	LC50: 63.4 - 73.6mg/L (96h, Pimephales promelas) LC50: =26mg/L (96h, Cyprinus carpio) LC50: =4.6mg/L (96h, Oncorhynchus mykiss)	-	-

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential**Bioaccumulation****Component Information**

Chemical name	Partition coefficient
Ethyl ether	0.82
DI-ISOPROPYL ETHER	2.4
PYRIDINE	0.65

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Ethyl ether	The substance is not PBT / vPvB
Naphtha (petroleum),hydrotreated light	The substance is not PBT / vPvB
DI-ISOPROPYL ETHER	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
n-Butane	The substance is not PBT / vPvB
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U	The substance is not PBT / vPvB
Propane	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB
PYRIDINE	The substance is not PBT / vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste from residues/unused Should not be released into the environment. Dispose of in accordance with local

products	regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	A145, A167, A802
ERG Code	10L

IMDG

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	63,190, 277, 327, 344, 381, 959
EmS-No.	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	No information available

RID

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	AEROSOL, FLAMMABLE
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	190, 327, 344, 625
Classification code	5A

ADR

14.1 UN number or ID number	UN1950
14.2 UN proper shipping name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	AEROSOL, FLAMMABLE
14.5 Environmental hazards	No
14.6 Special precautions for user	
Special Provisions	327, 625, 344, 190
Classification code	5A
Tunnel restriction code	(D)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations**Authorisations and/or restrictions on use:**

This product contains one or more substances subject to restriction (UK REACH - Annex XVII).

Chemical name	Restricted substance per REACH Annex XVII	Substance subject to authorisation per REACH Annex XIV
Naphtha (petroleum),hydrotreated light - 64742-49-0	Use restricted. See item 28. Use restricted. See item 29. Restricted Carcinogen 1B Restricted Mutagen 1B	-
n-Butane - 106-97-8	Use restricted. See item 28. Use restricted. See item 29. Restricted Carcinogen 1A Restricted Mutagen 1B	-
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U - 64742-52-5	Use restricted. See item 28. Restricted Carcinogen 1B	-
Propane - 74-98-6	Use restricted. See item 28. Use restricted. See item 29.	-
Isobutane - 75-28-5	Use restricted. See item 28. Use restricted. See item 29. Restricted Carcinogen 1A Restricted Mutagen 1B	-

Persistent Organic Pollutants

Not applicable

Export Notification requirements

Not applicable

Dangerous substance category per COMAH Regulations 2015 (as amended)

P3a - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

P3b - FLAMMABLE AEROSOLS

Named dangerous substances per COMAH Regulations 2015 (as amended)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Naphtha (petroleum),hydrotreated light - 64742-49-0	-	25000
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC; BASEOIL - U - 64742-52-5	-	25000

The Ozone-Depleting Substances Regulations 2015

Not applicable

The Biocidal Products Regulations 2001 (as amended)

Not applicable

The Water Environment (Water Framework Directive) (England and Wales) Regulations 2017 (as amended)

Not applicable

Poisons Act 1972 (Explosive Precursors) Regulations (as Amended)

Chemical name	Poisons and Explosive Precursors
Acetone	Explosive precursor, Reportable

International Inventories

TSCA	Contact supplier for inventory compliance status
DSL/NDL	Contact supplier for inventory compliance status
EINECS/ELINCS	Contact supplier for inventory compliance status
ENCS	Contact supplier for inventory compliance status
IECSC	Contact supplier for inventory compliance status
KECL	Contact supplier for inventory compliance status
PICCS	Contact supplier for inventory compliance status
AIIC	Contact supplier for inventory compliance status
NZIoC	Contact supplier for inventory compliance status

Legend:

TSCA	- United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL	- Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS	- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS	- Japan Existing and New Chemical Substances
IECSC	- China Inventory of Existing Chemical Substances
KECL	- Korean Existing and Evaluated Chemical Substances
PICCS	- Philippines Inventory of Chemicals and Chemical Substances
AIIC	- Australian Inventory of Industrial Chemicals
NZIoC	- New Zealand Inventory of Chemicals

15.2. Chemical safety assessment

Chemical Safety Report	No information available
-------------------------------	--------------------------

SECTION 16: Other information**Key or legend to abbreviations and acronyms used in the safety data sheet****Full text of H-Statements referred to under section 3**

EUH019	- May form explosive peroxides
EUH066	- Repeated exposure may cause skin dryness or cracking
H220	- Extremely flammable gas
H224	- Extremely flammable liquid and vapour
H225	- Highly flammable liquid and vapour
H302	- Harmful if swallowed
H304	- May be fatal if swallowed and enters airways
H312	- Harmful in contact with skin
H315	- Causes skin irritation
H319	- Causes serious eye irritation
H332	- Harmful if inhaled
H336	- May cause drowsiness or dizziness
H411	- Toxic to aquatic life with long lasting effects

Legend

SVHC: Substances of Very High Concern for Authorisation:

Legend Section 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitisers		

Classification procedure

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method

Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	On basis of test data
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australian National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 04/06/2024

This material safety data sheet complies with the requirements of UK REACH Regulations (SI 2019/758 as amended)
Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

UK SDS version information - XGHS

UL release:
GHS Revision 7
2022 Q1

United Kingdom

Partial process, including GHS Wizard, NO TW

Specific target organ toxicity — single exposure	Category 3
Category 3 Target organ effects: Narcotic effects.	

Full text of H-Statements referred to under section 3

EUH019 - May form explosive peroxides EUH066 - Repeated exposure may cause skin dryness or cracking H220 - Extremely flammable gas H224 - Extremely flammable liquid and vapour H225 - Highly flammable liquid and vapour H302 - Harmful if swallowed H304 - May be fatal if swallowed and enters airways H312 - Harmful in contact with skin H315 - Causes skin irritation H319 - Causes serious eye irritation H332 - Harmful if inhaled H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects

Chemical name	Classification according to GB CLP (SI 2020/1567 as amended)	Specific concentration limit (SCL)
Ethyl ether	(EUH019) (EUH066) Flam. Liq. 1 (H224) Acute Tox. 4 (H302) STOT SE 3 (H336)	
Naphtha (petroleum),hydrotreated light	Flam. Liq. 2 (H225) Skin Irrit. 2 (H315) STOT SE 3 (H336) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411)	
DI-ISOPROPYL ETHER	(EUH019) (EUH066) Flam. Liq. 2 (H225) STOT SE 3 (H336)	
Acetone	(EUH066) Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)	
n-Butane	Flam. Gas 1 (H220) Press. Gas ()	
Propane	Flam. Gas 1 (H220) Press. Gas (H280)	
Isobutane	Flam. Gas 1 (H220) Press. Gas	
PYRIDINE	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam. Liq. 2 (H225)	