

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.
Issue date: 07/05/2025 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : (FORCE) X61640 BUMPER & TRIM SHINE 400ML
Product code : 003054000027
Type of product : Detergent
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use, Professional use, Industrial use
Use of the substance/mixture : Car maintenance product

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

James Briggs Limited
Salmon Fields Royton
OL2 6HZ Oldham Manchester – Lancashire
T 0161 627 0101
sds@jamesbriggs.co.uk

1.4. Emergency telephone number

Emergency number : +44 (0) 161 620 5400

Country/Area	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to GB CLP (SI 2019:720 as amended)

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Harmful to aquatic life with long lasting effects.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML


Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

2.2. Label elements

Labelling according to GB CLP (SI 2019:720 as amended)

Hazard pictograms (GB CLP)



Signal word (GB CLP)

Contains

Hazard statements (GB CLP)

Precautionary statements (GB CLP)

Child-resistant fastening

Tactile warning

- : Danger
- : Propan-2-ol; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
- : H222 - Extremely flammable aerosol.
- : H229 - Pressurised container: May burst if heated.
- : H315 - Causes skin irritation.
- : H336 - May cause drowsiness or dizziness.
- : H412 - Harmful to aquatic life with long lasting effects.
- : P101 - If medical advice is needed, have product container or label at hand.
- : P102 - Keep out of reach of children.
- : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- : P211 - Do not spray on an open flame or other ignition source.
- : P251 - Do not pierce or burn, even after use.
- : P261 - Avoid breathing vapours, spray.
- : P271 - Use only outdoors or in a well-ventilated area.
- : P280 - Wear protective gloves.
- : P264 - Wash hands thoroughly after handling.
- : P332+P313 - If skin irritation occurs: Get medical advice, attention.
- : P312 - Call a POISON CENTER, doctor if you feel unwell.
- : P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.
- : P501 - Dispose of contents/ container in accordance with local regulations.
- : Not applicable
- : Not applicable

2.3. Other hazards

Component	
Substance(s) not meeting the PBT criteria of UK REACH regulation, in accordance with Annex XIII	Propan-2-ol (67-63-0), Dimethyl siloxane (63148-62-9), Ethanol (64-17-5), Turpentine, oil (8006-64-2), Diethyl phthalate (84-66-2), 2,6-di-tert-butyl-p-cresol (128-37-0), Styrene (100-42-5), n-hexane (110-54-3), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)
Substance(s) not meeting the vPvB criteria of UK REACH regulation, in accordance with Annex XIII	Propan-2-ol (67-63-0), Dimethyl siloxane (63148-62-9), Ethanol (64-17-5), Turpentine, oil (8006-64-2), Diethyl phthalate (84-66-2), 2,6-di-tert-butyl-p-cresol (128-37-0), Styrene (100-42-5), n-hexane (110-54-3), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)
Component	
Substance(s) not considered as endocrine disrupting. They are not included in the list established in accordance with Article 59(1) of UK REACH for having endocrine disrupting properties, nor identified as having endocrine disrupting properties in accordance with the criteria set out in GB BPR and GB PPP	Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene)(68476-85-7), Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Propan-2-ol(67-63-0), Dimethyl siloxane(63148-62-9), Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics(64742-49-0), n-hexane(110-54-3), Diethyl phthalate(84-66-2), Turpentine, oil(8006-64-2), Ethanol(64-17-5), 2,6-di-tert-butyl-p-cresol(128-37-0), Styrene(100-42-5)

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) substance with workplace exposure limit(s)	CAS-No.: 68476-85-7 EC-No.: 270-704-2 UK Index-No.: 649-202-00-6	≥ 50	Flam. Gas 1A, H220 Press. Gas
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6	10 – 20	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propan-2-ol substance with workplace exposure limit(s)	CAS-No.: 67-63-0 EC-No.: 200-661-7 UK Index-No.: 603-117-00-0	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Dimethyl siloxane	CAS-No.: 63148-62-9 EC-No.: 613-156-5	5 – 10	Aquatic Chronic 3, H412
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	CAS-No.: 64742-49-0 EC-No.: 927-510-4	3.5 – 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
n-hexane substance with workplace exposure limit(s)	CAS-No.: 110-54-3 EC-No.: 203-777-6 UK Index-No.: 601-037-00-0	0.25 – 0.5	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361f STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Diethyl phthalate substance with workplace exposure limit(s)	CAS-No.: 84-66-2 EC-No.: 201-550-6	0.1 – 0.2	Aquatic Chronic 3, H412
Turpentine, oil substance with workplace exposure limit(s)	CAS-No.: 8006-64-2 EC-No.: 232-350-7 UK Index-No.: 650-002-00-6	0.005 – 0.05	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethanol substance with workplace exposure limit(s)	CAS-No.: 64-17-5 EC-No.: 200-578-6 UK Index-No.: 603-002-00-5	0.0000001 – 0.005	Flam. Liq. 2, H225
2,6-di-tert-butyl-p-cresol substance with workplace exposure limit(s)	CAS-No.: 128-37-0 EC-No.: 204-881-4	0.0000001 – 0.005	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Name	Product identifier	%	Classification according to GB CLP (SI 2019:720 as amended)
Styrene substance with workplace exposure limit(s)	CAS-No.: 100-42-5 EC-No.: 202-851-5 UK Index-No.: 601-026-00-0	0.0000001 – 0.005	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h) STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
n-hexane	CAS-No.: 110-54-3 EC-No.: 203-777-6 UK Index-No.: 601-037-00-0	(5 ≤ C ≤ 100) STOT RE 2; H373

Product subject to CLP Annex I, item 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

Detergent Regulation (EC 648/2004)

Ingredient data sheet		
Component	CAS-No.	%
Petroleum gases, liquefied; Petroleum gas; [A complex combination of hydrocarbons produced by the distillation of crude oil. It consists of hydrocarbons having carbon numbers predominantly in the range of C3 through C7 and boiling in the range of approximately– 40°C to 80°C (– 40°F to 176°F).]	68476-85-7	≥10%
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		≥10%
ISOPROPYL ALCOHOL	67-63-0	1 - 10%
DIMETHICONE	63148-62-9	1 - 10%
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	1 - 10%
HEXANE	110-54-3	0.1 - 1%
DIETHYL PHTHALATE	84-66-2	0.1 - 1%
CITRAL	5392-40-5	<0.1%
METHYL HYDROGENATED ROSINATE	8050-15-5	<0.1%
TURPENTINE	8006-64-2	<0.1%
LIMONENE	5989-27-5	<0.1%
Reaction mass of 2-methylbutyl salicylate and pentyl salicylate		<0.1%
BENZYL BENZOATE	120-51-4	<0.1%
ALPHA-CEDRENE	469-61-4	<0.1%
4-TERT-BUTYLCYCLOHEXYL ACETATE	32210-23-4	<0.1%
[3R-(3α,3aβ,7β,8α)]-octahydro-3,8,8-trimethyl-6-methylene-1H-3a,7-methanoazulene	546-28-1	<0.1%
CEDROL	77-53-2	<0.1%
VETIVEROL	68129-81-7	<0.1%
CITRONELLAL	106-23-0	<0.1%
EUCALYPTOL	470-82-6	<0.1%
PINENE	80-56-8	<0.1%

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Ingredient data sheet		
Component	CAS-No.	%
BETA-CARYOPHYLLENE	87-44-5	<0.1%
MYRCENE	123-35-3	<0.1%
BETA-PINENES	127-91-3	<0.1%
HELIOTROPINE	120-57-0	<0.1%
BENZOIC ACID	65-85-0	<0.1%
ALCOHOL DENAT.	64-17-5	<0.1%
α -Guaiene	3691-12-1	<0.1%
2,6-DI-TERT-BUTYL-4-METHYLPHENOL	128-37-0	<0.1%
LONGIFOLENE	475-20-7	<0.1%
STYRENE	100-42-5	<0.1%
P-CRESOL	106-44-5	<0.1%

Labelling of contents	
Component	%
aliphatic hydrocarbons	≥30%
perfumes	
CITRAL	
LIMONENE	
BENZYL BENZOATE	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after inhalation	: None under normal conditions.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
Explosion hazard : Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Propan-2-ol (67-63-0)	
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA)	999 mg/m ³
	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Ethanol (64-17-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA (OEL TWA)	1920 mg/m ³
	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Turpentine, oil (8006-64-2)	
United Kingdom - Occupational Exposure Limits	
Local name	Turpentine
WEL TWA (OEL TWA)	566 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	850 mg/m ³
	150 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Diethyl phthalate (84-66-2)	
United Kingdom - Occupational Exposure Limits	
Local name	Diethyl phthalate
WEL TWA (OEL TWA)	5 mg/m ³
WEL STEL (OEL STEL)	10 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

2,6-di-tert-butyl-p-cresol (128-37-0)	
United Kingdom - Occupational Exposure Limits	
Local name	2,6-Di-tert-butyl-p-cresol
WEL TWA (OEL TWA)	10 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Styrene (100-42-5)	
United Kingdom - Occupational Exposure Limits	
Local name	Styrene
WEL TWA (OEL TWA)	430 mg/m ³
	100 ppm
WEL STEL (OEL STEL)	1080 mg/m ³
	250 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
n-hexane (110-54-3)	
United Kingdom - Occupational Exposure Limits	
Local name	n-Hexane
WEL TWA (OEL TWA)	72 mg/m ³
	20 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
United Kingdom - Occupational Exposure Limits	
Local name	Liquefied petroleum gas
WEL TWA (OEL TWA)	1750 mg/m ³
	1000 ppm
WEL STEL (OEL STEL)	2180 mg/m ³
	1250 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage (only applies if LPG contains more than 0.1% of buta-1,3-diene))
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection			
Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Skin and body protection	
Type	Standard
protective clothing	EN ISO 6530

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves					EN 374-2

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Colour	: Straw.
Odour	: Not available
Odour threshold	: Not available
pH	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flash point	: Not applicable
Explosive limits	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Relative vapour density at 20°C	: Not available
Relative density	: Not available
Density	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: < 20.5 mm²/s
Explosive properties	: Pressurised container: May burst if heated.

9.2. Other information

VOC content	: 575 g/l
Particle characteristics	: Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Propan-2-ol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Propan-2-ol (67-63-0)	
LD50 oral	4396 mg/kg bodyweight
LD50 dermal rabbit	12800 mg/kg Source: ECHA
LD50 dermal	12800 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	46600 mg/l
Dimethyl siloxane (63148-62-9)	
LD50 oral rat	> 17000 mg/kg Source: National Library of Medicine
LD50 dermal rabbit	> 2000 mg/kg Source: National Library of Medicine
Ethanol (64-17-5)	
LD50 oral rat	15010 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 14450 - 15560
LD50 oral	8300 mg/kg bodyweight Animal: mouse, Remarks on results: other:
Turpentine, oil (8006-64-2)	
LD50 oral rat	2620 mg/kg Source: ECHA
LD50 oral	5760 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 2000 mg/kg Source: ECHA
LD50 dermal	5010 mg/kg bodyweight
LC50 Inhalation - Rat	13.7 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 11,1 - 14,8
LC50 Inhalation - Rat (Dust/Mist)	3425 mg/l
LC50 Inhalation - Rat (Vapours)	9.97 mg/l/4h
2,6-di-tert-butyl-p-cresol (128-37-0)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
n-hexane (110-54-3)	
LD50 oral rat	24 ml/kg Source: ECHA
LD50 oral	> 16000 mg/kg bodyweight
LD50 dermal rabbit	> 3350 mg/kg Source: ECHA
LD50 dermal	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 17600 mg/l
LC50 Inhalation - Rat (Vapours)	259.354 mg/l Source: ECHA
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat, Remarks on results: other:
LC50 Inhalation - Rat	> 25.2 mg/l air Animal: rat
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight Animal: rat
LC50 Inhalation - Rat	> 23.3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Causes skin irritation.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Propan-2-ol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

2,6-di-tert-butyl-p-cresol (128-37-0)

NOAEL (chronic, oral, animal/male, 2 years)	25 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:
---	---

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

Propan-2-ol (67-63-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Styrene (100-42-5)

STOT-single exposure	Not classified
----------------------	----------------

n-hexane (110-54-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Ethanol (64-17-5)

NOAEL (subchronic, oral, animal/male, 90 days)	< 9700 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
--	--

NOAEL (subchronic, oral, animal/female, 90 days)	> 9400 mg/kg bodyweight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
--	--

Styrene (100-42-5)

STOT-repeated exposure	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
------------------------	--

n-hexane (110-54-3)

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)

LOAEC (inhalation, rat, gas, 90 days)	12000 ppm Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test), Guideline: other:
---------------------------------------	---

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)

LOAEC (inhalation, rat, vapour, 90 days)	16.6 mg/l air Animal: rat, Animal sex: male
--	---

NOAEC (inhalation, rat, vapour, 90 days)	3.3 mg/l air Animal: rat, Animal sex: male
--	--

Aspiration hazard	: Not classified
-------------------	------------------

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Vaporizer	Aerosol
-----------	---------

Viscosity, kinematic	< 20.5 mm²/s
----------------------	--------------

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML	
Not able to form a pool	Yes
Propan-2-ol (67-63-0)	
Viscosity, kinematic	2.658 mm²/s
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Viscosity, kinematic	0.7 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
Viscosity, kinematic	0.67 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'
Other information	

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Propan-2-ol (67-63-0)	
LC50 - Fish [1]	9640 mg/l
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	1000 mg/l
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea
EC50 - Other aquatic organisms [2]	> 1000 mg/l
ErC50 algae	1000 mg/l
NOEC chronic crustacea	100 mg/l
Dimethyl siloxane (63148-62-9)	
LC50 - Fish [1]	37.79 mg/l Source: The ECOTOXicology database
Ethanol (64-17-5)	
LC50 - Fish [1]	14.2 g/l Test organisms (species): Pimephales promelas
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'
Turpentine, oil (8006-64-2)	
LC50 - Fish [1]	29 mg/l
EC50 - Crustacea [1]	0.475 mg/l Source: ECHA
EC50 - Other aquatic organisms [1]	6.4 mg/l waterflea
EC50 - Other aquatic organisms [2]	17.1 mg/l
EC50 72h - Algae [1]	0.519 mg/l Source: ECHA

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Diethyl phthalate (84-66-2)	
EC50 96h - Algae [1]	85.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
2,6-di-tert-butyl-p-cresol (128-37-0)	
LC50 - Fish [1]	> 0.57 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	0.48 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.023 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-hexane (110-54-3)	
LC50 - Fish [1]	2.5 mg/l
EC50 - Crustacea [1]	3.88 mg/l
EC50 - Other aquatic organisms [1]	50 mg/l waterflea
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
LC50 - Fish [1]	0.362 mg/l
EC50 - Crustacea [1]	0.018 mg/l
ErC50 algae	7.6 mg/l Source: ECOTOX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
LOEC (chronic)	0.32 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.17 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
12.2. Persistence and degradability	
(FORCE) X61640 BUMPER & TRIM SHINE 400ML	
Persistence and degradability	Not rapidly degradable
Propan-2-ol (67-63-0)	
Persistence and degradability	Rapidly degradable
Biodegradation	95 %
Dimethyl siloxane (63148-62-9)	
Persistence and degradability	Not rapidly degradable
Ethanol (64-17-5)	
Persistence and degradability	Not rapidly degradable
Turpentine, oil (8006-64-2)	
Persistence and degradability	Not rapidly degradable
Diethyl phthalate (84-66-2)	
Persistence and degradability	Not rapidly degradable

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

2,6-di-tert-butyl-p-cresol (128-37-0)	
Persistence and degradability	Not rapidly degradable
Styrene (100-42-5)	
Persistence and degradability	Not rapidly degradable
n-hexane (110-54-3)	
Persistence and degradability	Not rapidly degradable
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Persistence and degradability	Not rapidly degradable
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Persistence and degradability	Rapidly degradable
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

Propan-2-ol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05
Turpentine, oil (8006-64-2)	
Partition coefficient n-octanol/water (Log Pow)	4.16 – 4.83 Source: HSDB
n-hexane (110-54-3)	
Partition coefficient n-octanol/water (Log Pow)	3.9
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	
Partition coefficient n-octanol/water (Log Pow)	≤ 2.8 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component	
Propan-2-ol (67-63-0)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Dimethyl siloxane (63148-62-9)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Ethanol (64-17-5)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII
Turpentine, oil (8006-64-2)	This product does not contain substances at ≥0.1% that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at ≥0.1% that meet the vPvB criteria of UK REACH regulation, annex XIII

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Component	
Diethyl phthalate (84-66-2)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
2,6-di-tert-butyl-p-cresol (128-37-0)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Styrene (100-42-5)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
n-hexane (110-54-3)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Petroleum gases, liquefied (Contains < 0.1% 1,3-butadiene) (68476-85-7)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (64742-49-0)	This product does not contain substances at $\geq 0.1\%$ that meet the PBT criteria of UK REACH regulation, annex XIII This product does not contain substances at $\geq 0.1\%$ that meet the vPvB criteria of UK REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

HP Code

: HP3 - "Flammable:"
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.
HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Transport document description				
UN 1950, 2.1, (D)	UN 1950 , 2.1	UN 1950 , 2.1	UN 1950 , 2.1	UN 1950 , 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: False	Dangerous for the environment: False Marine pollutant: No	Dangerous for the environment: False	Dangerous for the environment: False	Dangerous for the environment: False
No supplementary information available				

14.6. Special precautions for user

Overland transport

Special provisions (ADR) : 190, 327, 344, 625
Packing instructions (ADR) : P207, LP200
Special packing provisions (ADR) : PP87, RR6, L2
Mixed packing provisions (ADR) : MP9

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12
Special provisions for carriage - Operation (ADR) : S2

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
Packing instructions (IMDG) : P207, LP200
Special packing provisions (IMDG) : PP87, L2
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

Special provisions (IATA) : A145, A167, A802

Inland waterway transport

Special provisions (ADN) : 190, 327, 344, 625
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01, VE04

Rail transport

Special provisions (RID) : 190, 327, 344, 625
Packing instructions (RID) : P207, LP200
Special packing provisions (RID) : PP87, RR6, L2
Mixed packing provisions (RID) : MP9
Special provisions for carriage – Packages (RID) : W14
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12
Colis express (express parcels) (RID) : CE2

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. National regulations

UK REACH Annex XVII (Restriction List)

This product contains no substance(s) listed on UK REACH Annex XVII (Restriction List) equal to or above the level of SDS disclosure

UK REACH Annex XIV (Authorisation List)

This product contains no substance(s) listed on UK REACH Annex XIV (Authorisation List) equal to or above the 0.1% level of disclosure

UK REACH Candidate List (SVHC)

This product contains no substance(s) listed on the UK REACH Candidate List (SVHC) above the 0.1% level of disclosure

Detergent Regulation (EC 648/2004)

Fragrance allergens > 0.01%:

CITRAL
LIMONENE
BENZYL BENZOATE

GB PIC regulation (Prior Informed Consent)

This product contains no substance(s) listed on the GB PIC List equal to or above the level of SDS disclosure

POP Regulation (Persistent Organic Pollutants)

This product contains no substance(s) listed on the GB POP List equal to or above the level of SDS disclosure

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Ozone Regulation (S.I. No. 168 of 2015)

This product contains no substance(s) listed on the GB Ozone Depletion List equal to or above the level of SDS disclosure

Control of Poisons and Explosives Precursors Act

This product contains no substance(s) listed as a reportable poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This product contains no substance(s) listed as a reportable explosive precursor on the Control of Poisons and Explosives Precursors Regulations equal to or above the level of SDS disclosure

This substance is not listed as a regulated poison on the Control of Poisons and Explosives Precursors Regulations

Drug Precursors Regulation (EC 273/2004)

This product contains no substance(s) listed on the GB Drug Precursors List equal to or above the level of SDS disclosure

15.1.2. Other Information

VOC content : 575 g/l

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
BS EN	British Standard
CAS-No.	Chemical Abstract Service number
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Abbreviations and acronyms:

N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas	Gases under pressure
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

(FORCE) X61640 BUMPER & TRIM SHINE 400ML

Safety Data Sheet

According to REACH Regulation (EC) No 1907/2006, as retained and amended in UK law, and based on EU 2015/830.

Full text of H- and EUH-statements:	
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), UK

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.