



SAFETY DATA SHEET

STP® Engine Flush

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Engine Flush
Product number 62450

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Oil additive. Engine cleaner.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd
 Sword House
 Totteridge Road
 High Wycombe
 HP13 6DG
 UK
 Tel: +44 845 602 1995
 euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234
 Monday - Thursday: 0830 - 1700
 Friday: 0830 - 1530

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified
Health hazards Asp. Tox. 1 - H304
Environmental hazards Not Classified

Human health Pneumonia may be the result if vomited material containing solvents reaches the lungs.

2.2. Label elements

Hazard pictograms



Signal word Danger
Hazard statements H304 May be fatal if swallowed and enters airways.

STP® Engine Flush

Precautionary statements P101 If medical advice is needed, have product container or label at hand.
P405 Store locked up.
P102 Keep out of reach of children.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Detergent labelling ≥ 30% aliphatic hydrocarbons

Supplementary precautionary statements P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS number: 64742-47-8 EC number: 926-141-6	50 - 100%
Classification Asp. Tox. 1 - H304	
1,2-diaminoethane CAS number: 107-15-3 EC number: 203-468-6 Substance of very high concern (SVHC).	<0.025%
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Acute Tox. 3 - H311 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Resp. Sens. 1B - H334 Skin Sens. 1B - H317 Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Inhalation If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

STP® Engine Flush

Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Drowsiness. Dizziness.
Ingestion	May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Keep affected person under observation.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all ignition sources if safe to do so. Avoid contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

STP® Engine Flush

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open flame. Provide adequate ventilation.

Advice on general occupational hygiene Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

1,2-diaminoethane

Long-term exposure limit (8-hour TWA): WEL 10 ppm 25 mg/m³

WEL = Workplace Exposure Limit.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-47-8)

DNEL Not determined.

PNEC Not determined.

Distillates (petroleum), hydrotreated heavy paraffinic (CAS: 64742-54-7)

DNEL Workers - Inhalation; Long term local effects: 5.6 mg/m³
General population - Inhalation; Long term local effects: 1.2 mg/m³

PNEC Oral; 9.33 mg/kg

8.2. Exposure controls

STP® Engine Flush

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked.

Environmental exposure controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Straw.
Odour	Characteristic.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not relevant.
Initial boiling point and range	Not determined.
Flash point	70°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Vapour pressure	Not determined.
Vapour density	Not determined.

STP® Engine Flush

Relative density	0.8242
Bulk density	822.7 kg/m ³
Partition coefficient	Not determined.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.
Viscosity	3.02 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Other information	No information required.
-------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

Skin corrosion/irritation

Skin corrosion/irritation	Based on available data the classification criteria are not met.
---------------------------	--

Serious eye damage/irritation

STP® Engine Flush

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Kinematic viscosity $\leq 20.5 \text{ mm}^2/\text{s}$. May be fatal if swallowed and enters airways.

Skin contact Repeated exposure may cause skin dryness or cracking.

Toxicological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Read-across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 4,951.0

Species Rat

STP® Engine Flush

Notes (inhalation LC₅₀)	REACH dossier information. Read-across data.
ATE inhalation (vapours mg/l)	4,951.0
<u>Skin corrosion/irritation</u>	
Animal data	Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Read-across data.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-across data.
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information. Read-across data.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information. Read-across data.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEC 1100 mg/m ³ , Inhalation, Mouse REACH dossier information. Read-across data.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH dossier information. Read-across data.
Reproductive toxicity - development	Maternal toxicity: - NOAEL: >= 5220 mg/m ³ , Inhalation, Rat REACH dossier information.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEC > 10400 mg/m ³ , Inhalation, Rat REACH dossier information. Read-across data.
<u>Aspiration hazard</u>	
Aspiration hazard	2.4 cSt @ 20°C Asp. Tox. 1 - H304
<u>1,2-diaminoethane</u>	
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	866.0
Species	Rat
Notes (oral LD₅₀)	REACH dossier information.
ATE oral (mg/kg)	866.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	560.0
Species	Rabbit

STP® Engine Flush

Notes (dermal LD₅₀)	REACH dossier information.
ATE dermal (mg/kg)	560.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	14.7
Species	Rat
Notes (inhalation LC₅₀)	REACH dossier information.
ATE inhalation (vapours mg/l)	14.7
<u>Skin corrosion/irritation</u>	
Animal data	Dose: 2.5 x 2.5 cm, 1, 5, 15 minutes, Rabbit Erythema/eschar score: Moderate to severe erythema (3). REACH dossier information. Skin Corr. 1B - H314
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Dose: 50 µl, 1 second, Rabbit REACH dossier information. Eye Dam. 1 - H318
<u>Skin sensitisation</u>	
Skin sensitisation	Guinea pig maximization test (GPMT) - Guinea pig: Sensitising. REACH dossier information.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEL 9 mg/kg/day, Oral, Rat REACH dossier information.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL 227 mg/kg/day, Oral, Rat F1 REACH dossier information.
Reproductive toxicity - development	Maternal toxicity: - LOAEL: 454 mg/kg/day, Oral, Rat REACH dossier information.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 22 mg/kg/day, Oral, Rat REACH dossier information.
<u>Aspiration hazard</u>	
Aspiration hazard	1.265 - 1.725 mPa s @ 25°C/77°F REACH dossier information.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Not considered toxic to fish. However, large or frequent spills may have hazardous effects on the environment.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

STP® Engine Flush

Acute toxicity - fish	LL ₅₀ , 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.
Acute toxicity - aquatic invertebrates	EL ₅₀ , 48 hours: > 1000 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EL ₅₀ , 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.
<u>Chronic aquatic toxicity</u>	
Chronic toxicity - fish early life stage	NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout) QSAR REACH dossier information.
Chronic toxicity - aquatic invertebrates	NOELR, 21 days: 1.22 mg/l, Daphnia magna QSAR REACH dossier information.

1,2-diaminoethane

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 96 hours: 640 mg/l, Poecilia reticulata (Guppy) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 16.7 mg/l, Daphnia magna REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 645 mg/l, Pseudokirchneriella subcapitata REACH dossier information.
Acute toxicity - microorganisms	EC ₅₀ , 2 hours: 3.2 mg/l, Nitrifying bacteria REACH dossier information.
<u>Chronic aquatic toxicity</u>	
Chronic toxicity - fish early life stage	NOEC, 28 days: > 10 mg/l, Gasterosteus aculeatus (Three-spined stickleback) REACH dossier information.
Chronic toxicity - aquatic invertebrates	NOEC, 21 days: 0.16 mg/l, Daphnia magna REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation	Water - Degradation ~ 5%: 3 days Water - Degradation 69: 28 days REACH dossier information. Readily biodegradable but failing the 10-day window.
-----------------------	---

1,2-diaminoethane

Persistence and degradability	REACH dossier information. Read-across data.
--------------------------------------	--

STP® Engine Flush

Phototransformation	Water - DT ₅₀ : 6.076 hours REACH dossier information. QSAR
Biodegradation	Water - Degradation (95%): 28 days REACH dossier information. The substance is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Partition coefficient Scientifically unjustified. REACH dossier information.

1,2-diaminoethane

Partition coefficient log Pow: -4.42 REACH dossier information. QSAR

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Mobility The product has poor water-solubility.

Surface tension 26.4 mN/m @ 25°C

1,2-diaminoethane

Adsorption/desorption coefficient Water - log Koc: 3.68 @ 25°C/77°F REACH dossier information.

Henry's law constant 0.6 Pa m³/mol @ 25°C/77°F REACH dossier information. Estimated value.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

SECTION 14: Transport information

STP® Engine Flush

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78
and the IBC Code**

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

EH40/2005 Workplace exposure limits.

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use)

(Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.

IMDG: International Maritime Dangerous Goods.

IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ATE: Acute Toxicity Estimate.

DNEL: Derived No Effect Level.

LC50: Lethal Concentration to 50 % of a test population.

LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

STP® Engine Flush

Classification procedures according to SI 2019 No. 720	Asp. Tox. 1 - H304: Calculation method., Expert judgement.
Revision comments	Section 15: Regulatory information // 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.
Revision date	18/08/2021
Revision	15
Supersedes date	24/02/2021
SDS number	300
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H311 Toxic in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H412 Harmful to aquatic life with long lasting effects.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.