

SAFETY DATA SHEET

ANTI FOG

Page: 1

Compilation date: 20/11/2020

Revision No: 2.01

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ANTI FOG

Product code: LC115

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: Carchem

Unit 1

Park Road East

Calverton

Nottinghamshire

NG14 6LL

United Kingdom

Tel: +44 (0) 844 414 0987

Email: info@car-chem.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 844 414 0987

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315

Most important adverse effects: Flammable liquid and vapour. Causes skin irritation. Causes serious eye damage. May cause drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H336: May cause drowsiness or dizziness.

Hazard pictograms: GHS02: Flame

GHS05: Corrosion

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET

ANTI FOG

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+352: IF ON SKIN: Wash with plenty of water/and soap.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	30-80%

HYDROCARBONS, C13-C16, N-ALKANES, ISOALKANES, CYCLICS, <0.03% AROMATICS - REACH registered number(s): 01-2119826592-36-XXXX

934-954-2	-	Substance with a Community workplace exposure limit.	Asp. Tox. 1: H304	1.9-5%
-----------	---	--	-------------------	--------

DICOCOALKYLDIMETHYLAMMONIUM CHLORIDE

263-087-6	61789-77-3	-	Acute Tox. 4: H302; Skin Corr. 1B: H314; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 2: H411	1.9-5%
-----------	------------	---	---	--------

ETHYLENE GLYCOL - REACH registered number(s): 01-2119456816-28-XXXX

203-473-3	107-21-1	-	Acute Tox. 4: H302	1-1.9%
-----------	----------	---	--------------------	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

SAFETY DATA SHEET

ANTI FOG

Page: 3

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Prolonged and repeated exposure to solvents can lead to skin dryness and cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel.
Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

[cont...]

SAFETY DATA SHEET

ANTI FOG

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.
Suitable packaging: It is recommended to store in original packaging

7.3. Specific end use(s)

Specific end use(s): PC35: Washing and cleaning products (including solvent based products).

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPAN-2-OL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-

HYDROCARBONS, C13-C16, N-ALKANES, ISOALKANES, CYCLICS, <0.03% AROMATICS

EU	5mg/m3	10mg/m3	-	-
----	--------	---------	---	---

ETHYLENE GLYCOL

UK	52 mg/m3 (vapour)	104 mg/m3 (vapour)	-	-
----	-------------------	--------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Wear Nitrile Gloves of minimum thickness 0.5mm. Gloves should be replaced regularly or if any change in appearance is noticed. Ensure gloves are manufactured/tested in accordance with BS EN 374. Penetration times carried out according to EN 374 part III are not always practical, therefore max. wearing time of 50% of penetration time is recommended.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: An environmental assessment must be made to ensure compliance with local environmental legislation.

SAFETY DATA SHEET

ANTI FOG

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Odour: Alcoholic

Solubility in water: Miscible

Viscosity: Non-viscous

Flash point°C: ~25

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

SAFETY DATA SHEET

ANTI FOG

ETHYLENE GLYCOL

IVN	RAT	LD50	3260	mg/kg
ORL	MUS	LD50	5500	mg/kg
ORL	RAT	LD50	4700	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Prolonged and repeated exposure to solvents can lead to skin dryness and cracking.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

SAFETY DATA SHEET

ANTI FOG

Page: 7

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.
(PROPAN-2-OL)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: EU Legislation Regulation (EC) No 1907/2006 REACH. Regulation (EC) No 1272/2008 CLP. This mixture may be classed as a detergent due to its intended use and we expect it to comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents, based on details of the individual chemicals.
Guidance Notes: Workplace Exposure Limits EH40

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

[cont...]

SAFETY DATA SHEET

ANTI FOG

Page: 8

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.