

SAFETY DATA SHEET

FIXT Air Tool Oil

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FIXT Air Tool Oil

Product number FX081305

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC24 Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Supplier Seymour Road
Nuneaton
Warwickshire
CV11 4LB

02476 322 196 (T)
02476 322 117 (F)
info@fixtconsumables.com

1.4. Emergency telephone number

Emergency telephone 02476 322 196

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Human health In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea.

Environmental This product contains substances which are very toxic or toxic to aquatic organisms and may cause long term effects to the aquatic environment (see sections 2 and 12)

Physicochemical Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

FIXT Air Tool Oil

Precautionary statements	P102 Keep out of reach of children.
	P501 Dispose of contents/container in accordance with local regulations.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260 Do not breathe vapours.
	P271 Use only outdoors or in a well-ventilated area.
	P308+P313 IF exposed or concerned: Get medical advice/attention.
	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
	P410 Protect from sunlight.

Supplemental label information	RCH002b For professional users only.
---------------------------------------	--------------------------------------

Contains	KEROSENE
-----------------	----------

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

KEROSENE			30-60%
CAS number: 8008-20-6	EC number: 232-366-4	REACH registration number: 01-2119485517-27	
Classification		Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226		Xn;R65. N;R51/53. R10.	
Skin Irrit. 2 - H315			
STOT SE 3 - H336			
Asp. Tox. 1 - H304			
Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments	Blend of mineral oils with multifunctional additives.
-----------------------------	-------------------------------------------------------

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical advice/attention if you feel unwell. Remove affected person from source of contamination.
Inhalation	If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Get medical attention if any discomfort continues. Do not induce vomiting. Avoid vomiting and stomach flushing because of the risk of aspiration. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Continue to rinse for at least 15 minutes and get medical attention.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

FIXT Air Tool Oil

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. Contains Petroleum.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide or dry powder. Use water spray to cool containers.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Special protective equipment for firefighters Use air-supplied respirator, gloves and protective goggles. Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. To prevent release, place container with damaged side up.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb spillage with sand or other inert absorbent. Collect and place in suitable waste disposal containers and seal securely. Provide adequate ventilation.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Avoid spilling. Avoid contact with skin and eyes. Avoid inhalation of vapours and spray/mists. Contaminated clothing and shoes must be discarded. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

7.3. Specific end use(s)

FIXT Air Tool Oil

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

KEROSENE

Long-term exposure limit (8-hour TWA): SUP 600 mg/m³

Ingredient comments No exposure limits known for ingredient(s).

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation.

Personal protection When using do not smoke

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection Use protective gloves.

Other skin and body protection Provide eyewash station. Wear apron or protective clothing in case of contact.

Hygiene measures Provide eyewash station. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Odour	Solvent.
Flash point	70°C
Vapour pressure	<0.1 kPa @ °C
Relative density	0.8 @ 20°C
Solubility(ies)	Insoluble in water.
Viscosity	<7 cSt @ 20°C
Explosive properties	Not considered to be explosive. Vapours may form explosive mixtures with air.
Comments	Information given is applicable to the major ingredient.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

FIXT Air Tool Oil

10.1. Reactivity

Reactivity Stable at normal ambient temperatures and when used as recommended.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid Keep away from oxidising materials, heat and flames.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at ambient temperature.
Ingestion	May cause irritation. Symptoms following overexposure may include the following: Stomach pain. Nausea, vomiting. Diarrhoea.
Skin contact	Skin irritation should not occur when used as recommended. Prolonged contact may cause dryness of the skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.
Acute and chronic health hazards	Because of the product's quantity and composition, the health hazard is regarded as low.
Route of entry	Skin and/or eye contact
Target organs	Eyes Skin

SECTION 12: Ecological Information

Ecotoxicity This product has not been tested but contains ingredients which are toxic or very toxic to aquatic organisms and may cause long term adverse effects in the aquatic environment. During normal use the volatility of the components and the packaging form, pressurised container, make entry into the aquatic environment unlikely, however, do not empty or discharge into drains or watercourses. Ensure container is empty before disposal to prevent contents entering watercourses.

12.1. Toxicity

Toxicity Not available.

12.2. Persistence and degradability

Persistence and degradability Not available.

12.3. Bioaccumulative potential

FIXT Air Tool Oil

Bioaccumulative potential Not available.

12.4. Mobility in soil

Mobility Not known.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not available.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General Packs of 5L and under are not regulated under the Limited Quantities Provisions.

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (ADN) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS KEROSENE)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS KEROSENE)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS KEROSENE)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS KEROSENE)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID classification code M6

ADR/RID label 9

IMDG class 9

ICAO class/division 9

ADN class 9

FIXT Air Tool Oil

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EU legislation	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	Revised formulation. Revised classification.
Revision date	19/05/2016

FIXT Air Tool Oil

Revision	3
SDS number	12418
SDS status	Approved.
Risk phrases in full	Not classified.
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.